

GENIE GENERATORS T T25I ISUZU 4LE1



ENGINE Isuzu 4LE1
Capacity: 6,7 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Check every 10 hours, change every 250 hours

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 10 hours, change every 250 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40

Check every 10 hours, change every 250 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20

PRODUCT RECOMMENDATION 2

Multifleet SCD 10W

Check every 10 hours, change every 250 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Check every 10 hours, change every 50 hours

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 10 hours, change every 50 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40

Check every 10 hours, change every 50 hours

GENIE GENERATORS T T25I ISUZU 4LE1

| USE | | CLIMATE |
|--|---------------------------|---------|
| Initial service | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 20W-20 | Multifleet SCD 10W | |
| <i>Check every 10 hours, change every 50 hours</i> | | |

| COOLING SYSTEM | | |
|---|--------------------------|----------|
| Capacity: 3,8 liter | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| <i>Check every 10 hours, change every 12 months</i> | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.