GENIE SCISSOR LIFTS, SELF PROPELLED ELECTRIC GS/V GS-3246 (GS4604-60000 -> GS4605-75437)



HYDRAULIC SYSTEM

	•		
Perlus H 46	Perlus H 32	Perlus AF 46	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Normal		Moderate	
USE		CLIMATE	
Capacity: 19 liter (Hydraulic system including tank), Capacity: 14,2 liter (Hydraulic tank)			

Check every 250 hours/ 3 months, change every 24 months/ 2000 hours

GREASE POINTS/NIPPLES STEERING YOKES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		
Change every 100 hours		

Change every 100 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.