

# GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3268 RT KUBOTA D- 905 TIER 2, (43886 - 44770) (TILL 2007)



**ENGINE** Kubota D905 Tier 2  
Capacity: 5,1 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

*Check every 10 hours, change every 200 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20**

*Check every 10 hours, change every 200 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Kroontrak MTH 10W-30**

*Check every 10 hours, change every 200 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

*Check every 10 hours, change every 200 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

*Check every 10 hours, change every 50 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20**

*Check every 10 hours, change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Kroontrak MTH 10W-30**

*Check every 10 hours, change every 50 hours*

## PRODUCT RECOMMENDATION

# GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3268 RT KUBOTA D- 905 TIER 2, (43886 - 44770) (TILL 2007)



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		
<i>Check every 10 hours, change every 50 hours</i>		

HYDRAULIC SYSTEM		
Capacity: 64,4 liter (Complete), Capacity: 56,8 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	
<i>Check every 250 hours, change every 2000 hours/ 24 months</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

COOLING SYSTEM		
Capacity: 3,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	
<i>Check every 10 hours, change every 24 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.