GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT DEUTZ D2011 L03I (40297 - 40832) (2008 AND



USE Preferred, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Preferred, normal load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE VCLIMATE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Moderate CLIMATE Moderate Moderate	ENGINE Deutz D 2011 L03i Capacity: 8 liter, Capacity: 6 liter (Cha	nge capacity)	
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Preferred, normal load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load Reconcer recommendation 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean		igo oupuony,	CLIMATE
Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Preferred, normal load Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean	Preferred, high load		Moderate
Check every 10 hours, change every 500 hours/ 12 months USE Preferred, normal load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean	PRODUCT RECOMMENDATION 1		
Preferred, normal load Product recommendation 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load Moderate PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate Moderate PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate Moderate PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moditerranean	Agrisynth LSP 10W-40		
Preferred, normal load Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean	Check every 10 hours, change every	500 hours/ 12 months	
RRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE NORMAL White SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE NORMAL NORMAL RRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE NORMAL RRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE NORMAL Normal, high load Mediterranean Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE NORMAL, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE NORMAL, high load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean Mediterranean			
Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE NOrmal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE NOrmal Moderate Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE NOrmal PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE NOrmal, high load Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Mediterranean	Preferred, normal load		Moderate
Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE NOrmal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE NOrmal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE NOrmal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean Mediterranean			
Normal Normal Normal Noutificet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Normal Noutificet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load Noderate PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Normal PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean CLIMATE Mediterranean Mediterranean	Agrisynth LSP 10W-40		
Normal PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 2 Moderate Moditerranean CLIMATE Moditerranean CLIMATE Moderate PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean CLIMATE Mediterranean	Check every 8 hours, change every 12	2 months/ 1000 hours	
PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE NORMAL, high load Moderate PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE NORMAL, high load PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean			
Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean	Normal		Mediterranean
Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Normal, high load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Normal, high load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean Mediterranean			
Normal Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean Mediterranean	Multifleet SHPD 20W-50		
Normal Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moditerranean PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean Mediterranean	Check every 8 hours, change every 12	2 months/ 1000 hours	
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Additernative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean CLIMATE Mediterranean	USE		CLIMATE
Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE USE Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	Normal		Moderate
Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
CLIMATE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months Kroontrak CVT 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean Mediterranean	Check every 8 hours, change every 12	2 months/ 1000 hours	
Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months use Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months use CLIMATE Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months use CLIMATE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	USE		CLIMATE
Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 CLIMATE Mediterranean	Normal, high load		Mediterranean
Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 CLIMATE Mediterranean	PRODUCT RECOMMENDATION 1		
Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Climate CLIMATE Mediterranean	Multifleet SHPD 20W-50		
Normal, high load PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1	Check every 10 hours, change every	500 hours/ 12 months	
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	USE		CLIMATE
Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months use Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 CLIMATE Mediterranean	Normal, high load		Moderate
Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Alternative (acceptable), normal load Mediterranean PRODUCT RECOMMENDATION 1	Check every 10 hours, change every	500 hours/ 12 months	
PRODUCT RECOMMENDATION 1	USE		CLIMATE
	Alternative (acceptable), normal	load	Mediterranean
Multifleet SHPD 20W-50	PRODUCT RECOMMENDATION 1		
		500 hours/ 12 months	

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT DEUTZ D2011 L03I (40297 - 40832) (2008 AND



AFTER) Alternative (acceptable), normal load		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40
Check every 10 hours, change every 500	hours/ 12 months	
USE		CLIMATE
Alternative (acceptable), high load		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every 6 mg	onths/ 250 hours	
USE		CLIMATE
Alternative (acceptable), high load		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40

HUB REDUCTIONS Capacity: 0,5 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 12 months

Check every 10 hours, change every 6 months/ 250 hours

Check every 250 hours, change every 2000 hours/ 24 months		
Perlus H 46	Perlus H 32	Perlus AF 46
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable)		Moderate
USE		CLIMATE
Check every 250 hours, change ev	ery 2000 hours/ 24 months	
SP Matic 2032	ATF Almirol	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE

HYDRAULIC SYSTEM

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT DEUTZ D2011 L03I (40297 - 40832) (2008 AND



OREASE FOINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.