GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT DEUTZ F3L 1011F (40297 -) (2008 AND AFTER)



Preferred, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 500 hours/ 12 months USE Preferred, normal load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 CLIMATE Normal PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Recommendation 3 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 CLIMATE Mediterranean Mediterranean Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50	ENGINE Deutz F3L-1011F Capacity: 8 liter		
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Preferred, normal load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 1 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate CLIMATE Moderate PRODUCT RECOMMENDATION 1 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate CLIMATE Moderate Moderate CLIMATE Moderate Moderate CLIMATE Moderate Moderate CLIMATE Moderate Moderate Normal Agrisynth MSP 10W-40 Moderate PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 Moderate Mode			CLIMATE
Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Preferred, normal load Moderate Moderate Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Moderate CLIMATE Moderate Moderate CLIMATE Moderate Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Moderate Normal, high load PRODUCT RECOMMENDATION 1 Moderate Normal, high load PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moditerranean	Preferred, high load		Moderate
Check every 10 hours, change every 500 hours/ 12 months USE Preferred, normal load Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Rediterranean Mediterranean Check every 8 hours, change every 12 months/ 1000 hours USE Normal Rediterranean CLIMATE Mediterranean Mediterranean CLIMATE Moderate CLIMATE Moderate Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Reproduct recommendation 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load Reproduct recommendation 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load Reproduct recommendation 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load Reproduct recommendation 1 Moderate Moderate Moderate Moderate Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load Reproduct recommendation 2 Kroontrak CVT 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load Moderate Moderate Moderate Moderate Moderate Moderate Moderate Moderate Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load Rediterranean	PRODUCT RECOMMENDATION 1		
Preferred, normal load Moderate Preferred, normal load Moderate Product recommendation 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Moderate PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moditerranean	Agrisynth LSP 10W-40		
Preferred, normal load Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Moderate PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean	Check every 10 hours, change every 5	00 hours/ 12 months	
Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Moderate PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE CLIMATE Mediterranean Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean			
Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Moderate PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 CLIMATE Mediterranean Mediterranean CLIMATE Mediterranean Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 CLIMATE Moderate PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 1 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean	Preferred, normal load		Moderate
Check every 8 hours, change every 12 months/ 1000 hours USE Normal Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Moderate PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 1 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moditerranean Mediterranean			
Normal No	Agrisynth LSP 10W-40		
Normal PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE NOrmal PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE NOrmal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE NOrmal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean CLIMATE Mediterranean	Check every 8 hours, change every 12	months/ 1000 hours	
PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 2 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean CLIMATE Mediterranean	USE		CLIMATE
Multifleet SHPD 20W-50 Check every 8 hours, change every 12 months/ 1000 hours USE Normal Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Moderate PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	Normal		Mediterranean
Check every 8 hours, change every 12 months/ 1000 hours USE Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Normal, high load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1			
Normal Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1	Multifleet SHPD 20W-50		
Normal Normal PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean Mediterranean	Check every 8 hours, change every 12	months/ 1000 hours	
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Kroontrak CVT 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	USE		CLIMATE
Agrisynth LSP 10W-40 Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE USE Normal, high load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	Normal		Moderate
Check every 8 hours, change every 12 months/ 1000 hours USE Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Recommendation 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean Mediterranean	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1	Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Normal, high load PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months Kroontrak CVT 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean Mediterranean	Check every 8 hours, change every 12	months/ 1000 hours	
PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean	USE		CLIMATE
Multifleet SHPD 20W-50 Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean	Normal, high load		Mediterranean
Check every 10 hours, change every 500 hours/ 12 months USE Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Advised to the company of the compa			
Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 2 Kroontrak CVT 10W-40 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 CLIMATE Mediterranean	Multifleet SHPD 20W-50		
Normal, high load PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 CLIMATE Mediterranean	Check every 10 hours, change every 5	00 hours/ 12 months	
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40 CLIMATE Mediterranean	USE		CLIMATE
Agrisynth LSP 10W-40 Check every 10 hours, change every 500 hours/ 12 months USE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Agrisynth MSP 10W-40 CLIMATE Mediterranean	Normal, high load		Moderate
Check every 10 hours, change every 500 hours/ 12 months USE CLIMATE Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1	Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Alternative (acceptable), normal load PRODUCT RECOMMENDATION 1 Mediterranean	Check every 10 hours, change every 5	00 hours/ 12 months	
PRODUCT RECOMMENDATION 1	USE		CLIMATE
		oad	Mediterranean
Multifleet SHPD 20W-50	Alternative (acceptable), normal l		
	PRODUCT RECOMMENDATION 1	months/ 1000 hours	

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT DEUTZ F3L 1011F (40297 -) (2008 AND AFTER)

Check every 10 hours, change every 500 hours/ 12 months

Capacity: 132,5 liter (Complete), Capacity: 121 liter (Hydraulic tank)



use Alternative (acceptable), normal load	d	climate Moderate
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2		PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40
Check every 8 hours, change every 12 months/ 1000 hours		
USE		CLIMATE
Alternative (acceptable), high load		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every 500 hours/ 12 months		
use Alternative (acceptable), high load		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40

HUB REDUCTIONS Capacity: 0,5 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 12 months	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Check every 250 hours, change every 200	00 hours/ 24 months	
USE		CLIMATE
A1((* / ()))		
Alternative (acceptable)		Moderate
Alternative (acceptable) PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	PRODUCT RECOMMENDATION 2 Perlus H 32	

HYDRAULIC SYSTEM

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT DEUTZ F3L 1011F (40297 -) (2008 AND AFTER)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.