

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT FORD LRG- 425EFI (40833 -) (2008 AND AFTER)



ENGINE Ford LRG-425 EFI
Capacity: 4,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Synfleet SHPD 10W-40

Check every 10 hours, change every 200 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

Check every 10 hours, change every 200 hours

HUB REDUCTIONS

Capacity: 0,77 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 1000 hours/ 12 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Change every 150 hours

HYDRAULIC SYSTEM

Capacity: 114 liter (Hydraulic tank), Capacity: 142 liter (System, with outriggers), Capacity: 129,6 liter (System, without outriggers)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Check every 250 hours, change every 2000 hours/ 24 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus H 32

PRODUCT RECOMMENDATION 3

Perlus AF 46

Check every 250 hours, change every 2000 hours/ 24 months

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-3384 RT FORD LRG- 425EFI (40833 -) (2008 AND AFTER)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 10,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 800 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.