

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-5390 RT DEUTZ D2011 L03I (47229 -) (2008 AND AFTER)



ENGINE Deutz D 2011 L03i
Capacity: 9 liter, Capacity: 7 liter (Change capacity)

USE	CLIMATE
Preferred, high load	Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Preferred, normal load	Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

Check every 8 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SHPD 20W-50

Check every 8 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40

Check every 8 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal, high load	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal, high load	Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Alternative (acceptable), normal load	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SHPD 20W-50

Check every 8 hours, change every 12 months/ 1000 hours

PRODUCT RECOMMENDATION

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-5390 RT DEUTZ D2011 L03I (47229 -) (2008 AND AFTER)



USE		CLIMATE
Alternative (acceptable), normal load		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40

Check every 8 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Alternative (acceptable), high load		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 20W-50		

Check every 10 hours, change every 500 hours/ 12 months

USE		CLIMATE
Alternative (acceptable), high load		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Helar 0W-40	Agridiesel CRD+ 15W-40

Check every 10 hours, change every 500 hours/ 12 months

HUB REDUCTIONS

Capacity: 0,77 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 114 liter (Hydraulic tank), Capacity: 146,7 liter (System, with outriggers)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	

Check every 250 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 32	Perlus AF 46

Check every 250 hours, change every 2000 hours/ 24 months

PRODUCT RECOMMENDATION

GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-5390 RT DEUTZ D2011 L03I (47229 -) (2008 AND AFTER)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.