

PRODUCT RECOMMENDATION

# GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-5390 RT FORD DSG- 423EFI (42686 -) (2008 AND AFTER)



**ENGINE** Ford DSG 423EFI  
Capacity: 3,8 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Synfleet SHPD 10W-40**

*Check every 10 hours, change every 200 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

*Check every 10 hours, change every 200 hours*

## HUB REDUCTIONS

Capacity: 0,77 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 250 hours, change every 1000 hours/ 12 months*

| USE               | CLIMATE  |
|-------------------|----------|
| First change only | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 150 hours*

## HYDRAULIC SYSTEM

Capacity: 114 liter (Hydraulic tank), Capacity: 146,7 liter (System, with outriggers)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

*Check every 250 hours, change every 2000 hours/ 24 months*

| USE                      | CLIMATE  |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus H 32**

PRODUCT RECOMMENDATION 3

**Perlus AF 46**

*Check every 250 hours, change every 2000 hours/ 24 months*

# GENIE SCISSOR LIFTS, SELF PROPELLED ROUGH TERRAIN GS-5390 RT FORD DSG- 423EFI (42686 -) (2008 AND AFTER)



## GREASE POINTS/NIPPLES

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Labora Grease**

### PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

### PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

## COOLING SYSTEM

Capacity: 9,5 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

### PRODUCT RECOMMENDATION 2

**Coolant -26**

*Check every 10 hours, change every 800 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*