PRODUCT RECOMMENDATION

# GENIE TELESCOPIC BOOMS, SELF PROPELLED S-... S-60X DEUTZ TD2011L04I (S60X10-21001->) (2012 AND AFTER)

**ENGINE** Deutz TD 2011 L04i
Capacity: 12,1 liter

| USE | | CLIMATE |
|---|---|---|
| Extended, fuel sulfur level <0,5 %, ambient temperature > -10°C | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SHPD 20W-50** | | |
| *Check every 8 hours, change every 12 months/ 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Extended, fuel sulfur level <0,5 %, ambient temperature > -10°C | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Kroontrak CVT 10W-40** | **Agrisynth MSP 10W-40** | **Agridiesel MSP 15W-40** |
| *Check every 8 hours, change every 12 months/ 1000 hours* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SHPD 20W-50** | | |
| *Check every 10 hours, change every 500 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Kroontrak CVT 10W-40** | **Helar 0W-40** | **Agridiesel CRD+ 15W-40** |
| *Check every 10 hours, change every 500 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Severe, fuel sulfur level <0,5 %, ambient temperature > -10°C | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SHPD 20W-50** | | |
| *Check every 10 hours, change every 250 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Severe, fuel sulfur level <0,5 %, ambient temperature > -10°C | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Kroontrak CVT 10W-40** | **Helar 0W-40** | **Agridiesel CRD+ 15W-40** |
| *Check every 10 hours, change every 250 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Severe, extended, fuel sulfur level <0,5 %, ambient temperature > -10°C | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SHPD 20W-50** | | |
| *Check every 10 hours, change every 500 hours/ 12 months* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# GENIE TELESCOPIC BOOMS, SELF PROPELLED S-... S-60X DEUTZ TD2011L04I (S60X10-21001->) (2012 AND AFTER)

| USE | CLIMATE |
|---|---|
| Severe, extended, fuel sulfur level <0,5 %, ambient temperature > -10°C | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Kroontrak CVT 10W-40** | **Agrisynth MSP 10W-40** | **Agridiesel MSP 15W-40** |

*Check every 10 hours, change every 500 hours/ 12 months*

## HUB REDUCTIONS
Capacity: 0,6 liter (each hub)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** |

*Check every 1 months/ 250 hours, change every 1000 hours/ 12 months*

| USE | CLIMATE |
|---|---|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** |

*Change every 150 hours*

## HYDRAULIC SYSTEM
Capacity: 208 liter (Complete), Capacity: 170 liter (Hydraulic tank)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **SP Matic 2032** | **ATF Almirol** |

*Check every 10 hours, change every 2000 hours/ 24 months*

| USE | CLIMATE |
|---|---|
| Biodegradable oil | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Perlus Biosynth 46** | **Perlus Biosynth 32** |

*Check every 10 hours, change every 2000 hours/ 24 months*

## GREASE POINTS/NIPPLES

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# GENIE TELESCOPIC BOOMS, SELF PROPELLED S-... S-60X DEUTZ TD2011L04I (S60X10-21001->) (2012 AND AFTER)

**TURNTABLE ROTATION GEAR**
Capacity: 1,2-1,3 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367