

GENIE TELESCOPIC BOOMS, SELF PROPELLED S-... S-60XC DEUTZ D2011L03I (S60XC10-21001->) (2012 AND AFTER)



ENGINE Deutz D 2011 L03i
Capacity: 9 liter

USE	CLIMATE
Extended, fuel sulfur level <0,5 %, ambient temperature > -10°C	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Check every 8 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Extended, fuel sulfur level <0,5 %, ambient temperature > -10°C	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel MSP 15W-40

Check every 8 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Helar 0W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Severe, fuel sulfur level <0,5 %, ambient temperature > -10°C	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Severe, fuel sulfur level <0,5 %, ambient temperature > -10°C	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Helar 0W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Severe, extended, fuel sulfur level <0,5 %, ambient temperature > -10°C	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours/ 12 months

GENIE TELESCOPIC BOOMS, SELF PROPELLED S-... S-60XC DEUTZ D2011L03I (S60XC10-21001->) (2012 AND AFTER)



USE		CLIMATE
Severe, extended, fuel sulfur level <0,5 %, ambient temperature > -10°C		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
<i>Check every 10 hours, change every 500 hours/ 12 months</i>		

HUB REDUCTIONS		
Capacity: 0,6 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Check every 1 months/ 250 hours, change every 1000 hours/ 12 months</i>		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Change every 150 hours</i>		

HYDRAULIC SYSTEM		
Capacity: 208 liter (Complete), Capacity: 170 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
<i>Check every 10 hours, change every 2000 hours/ 24 months</i>		

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus Biosynth 32	
<i>Check every 10 hours, change every 2000 hours/ 24 months</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GENIE TELESCOPIC BOOMS, SELF PROPELLED S-... S-60XC DEUTZ D2011L03I (S60XC10-21001->) (2012 AND AFTER)

**TURNTABLE ROTATION GEAR**

Capacity: 1,2-1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.