

GENIE TELEHANDLERS GTH/AGRI GTH-4014 PERKINS 1104D-E44T STAGE 3A (GTH401414-101 ->)



ENGINE Perkins 1104D-E44T
Capacity: 9,6 liter

| USE | CLIMATE |
|-----------------------------------|----------|
| Normal, fuel sulfur level < 0.5 % | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------------|-----------------------------------|-----------------------------|
| Agrisynth LSP Ultra FE 5W-30 | Agrisynth LSP Ultra 10W-40 | Agrisynth MSP 10W-40 |

Check every 10 hours, change every 500 hours/ 12 months

AXLE SINGLE DRIVE Carraro 26.27M FR
Capacity: 8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Agrifluid HT-Plus | Agrifluid HT | |

Check every 1 months/ 250 hours, change every 1000 hours/ 12 months

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Agrifluid HT-Plus | Agrifluid HT | |

Change every 150 hours

AXLE SINGLE DRIVE Carraro 26.27M RR
Capacity: 8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Agrifluid HT-Plus | Agrifluid HT | |

Check every 1 months/ 250 hours, change every 1000 hours/ 12 months

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Agrifluid HT-Plus | Agrifluid HT | |

Change every 150 hours

GENIE TELEHANDLERS GTH/AGRI GTH-4014 PERKINS 1104D-E44T STAGE 3A (GTH401414-101 ->)

**HUB REDUCTIONS FRONT**

Capacity: 0,8 liter (each hub)

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

Check every 1 months/ 250 hours, change every 1000 hours/ 12 months

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

Change every 150 hours

HUB REDUCTIONS REAR

Capacity: 0,8 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

Check every 1 months/ 250 hours, change every 1000 hours/ 12 months

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

Change every 150 hours

TRANSMISSION Carraro TB172/2 2/2

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

Check every 1 months/ 250 hours, change every 1000 hours/ 12 months

GENIE TELEHANDLERS GTH/AGRI GTH-4014 PERKINS 1104D-E44T STAGE 3A (GTH401414-101 ->)



HYDRAULIC SYSTEM

Capacity: 161 liter (Hydraulic system including tank), Capacity: 112 liter (Hydraulic tank)

| USE | | CLIMATE |
|---------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |

Check every 10 hours, change every 2000 hours/ 24 months

COOLING SYSTEM

Capacity: 17,4 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.