

# GENIE TELEHANDLERS GTH/AGRI GTH-6025 ER (19309 ->) - CUMMINS TURBO QSB4.5 TIER 3



**ENGINE** Cummins QSB4.5  
Capacity: 18 liter

| USE                          |                               | CLIMATE                     |
|------------------------------|-------------------------------|-----------------------------|
| Normal                       |                               | Moderate                    |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3    |
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Synfleet SHPD 10W-40</b> |

*Check every 10 hours, change every 500 hours*

**DIFFERENTIAL FRONT**  
Capacity: 8,5 liter

| USE                              |                             | CLIMATE                  |
|----------------------------------|-----------------------------|--------------------------|
| Normal                           |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 1 months/ 250 hours, change every 1000 hours/ 12 months*

**DIFFERENTIAL REAR**  
Capacity: 8,5 liter

| USE                              |                             | CLIMATE                  |
|----------------------------------|-----------------------------|--------------------------|
| Normal                           |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 1 months/ 250 hours, change every 1000 hours/ 12 months*

**GEARBOX**  
Capacity: 2,7 liter

| USE                              |                             | CLIMATE                  |
|----------------------------------|-----------------------------|--------------------------|
| Normal                           |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 1 months/ 250 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT**  
Capacity: 0,6 liter

| USE                              |                             | CLIMATE                  |
|----------------------------------|-----------------------------|--------------------------|
| Normal                           |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 1 months/ 250 hours, change every 1000 hours/ 12 months*

# GENIE TELEHANDLERS GTH/AGRI GTH-6025 ER (19309 ->) - CUMMINS TURBO QSB4.5 TIER 3



## HUB REDUCTIONS REAR

Capacity: 0,6 liter

| USE                              |                             | CLIMATE                  |
|----------------------------------|-----------------------------|--------------------------|
| Normal                           |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

Check every 1 months/ 250 hours, change every 1000 hours/ 12 months

## HYDRAULIC SYSTEM

Capacity: 230 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Tropical |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 68</b>       | <b>Perlus AF 68</b>      |          |

Check every 8 hours, change every 12 months/ 1000 hours

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |          |

Check every 8 hours, change every 12 months/ 1000 hours

| USE                      |                          | CLIMATE |
|--------------------------|--------------------------|---------|
| Normal                   |                          | Arctic  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |         |
| <b>Perlus H 22</b>       | <b>Perlus AF 32</b>      |         |

Check every 8 hours, change every 12 months/ 1000 hours

## COOLING SYSTEM

Capacity: 45 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

Check every 10 hours, change every 2000 hours/ 24 months

# GENIE TELEHANDLERS GTH/AGRI GTH-6025 ER (19309 ->) - CUMMINS TURBO QSB4.5 TIER 3



## TURNTABLE ROTATION GEAR

Capacity: 2,8 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Abacot MEP HD 150</b> | <b>Abacot MEP 150</b>    |          |

Check every 1 months/ 250 hours, change every 1000 hours/ 12 months

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*