

GENIE TELEHANDLERS GTH/AGRI GTH-844

DEUTZ, GTH0806A-8418 ->



ENGINE Deutz BF4-2012
Capacity: 11,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Check every 10 hours, change every 6 months/ 250 hours

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Helar 0W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40

Check every 10 hours, change every 6 months/ 250 hours

DIFFERENTIAL FRONT Dana 212
Capacity: 8,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

DIFFERENTIAL REAR Dana 212
Capacity: 5,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

GENIE TELEHANDLERS GTH/AGRI GTH-844

DEUTZ, GTH0806A-8418 ->

**HUB REDUCTIONS FRONT** Dana 212

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

HUB REDUCTIONS REAR Dana 212

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

TRANSMISSION Dana T12000 3/3

Capacity: 12,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

HYDRAULIC SYSTEM

Capacity: 129 liter (Hydraulic tank), Capacity: 189 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

COOLING SYSTEM

Capacity: 11,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.