

GRADALL WHEELED EXCAVATORS

XL4300 III DETROIT DIESEL OM904 T3

(4300000043 ->)



ENGINE Detroit Diesel (MB) OM904
Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SHPD 15W-40

Check every 10 hours, change every 600 hours

AXLE FRONT ZF 3070
Capacity: 9,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

Agrifluid HT

Check every 100 hours, change every 750 hours

AXLE REAR ZF 3070
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

Agrifluid HT

Check every 100 hours, change every 750 hours

HUB REDUCTIONS FRONT
Capacity: 2,5 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

Agrifluid HT

Check every 100 hours, change every 750 hours

HUB REDUCTIONS REAR
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

Agrifluid HT

Check every 100 hours, change every 750 hours

GRADALL WHEELED EXCAVATORS

XL4300 III DETROIT DIESEL OM904 T3

(4300000043 ->)

**SWING TRANSMISSION**

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Check every 50 hours, change every 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

*Change every 250 hours/ 1 months***TRANSMISSION POWERSHIFT ZF HL290 2/2**

Capacity: 2,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40	

*Check every 100 hours***HYDRAULIC SYSTEM**

Capacity: 246 liter (Hydraulic system including tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus	Agrifluid HT

*Check every 10 hours, change every 750 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
HT Q9 High Grade Grease	Labora Grease

GRADALL WHEELED EXCAVATORS

XL4300 III DETROIT DIESEL OM904 T3

(4300000043 ->)

**COOLING SYSTEM**

Capacity: 21,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 1500 hours

SWING BULL GEAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

TILT BULL GEAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Compound OGL	Compound OGL EP 0/1	

TILT GEARBOX

Capacity: 0,9-1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.