

GRADALL MATERIAL HANDLERS 534B-8

**ENGINE**

Capacity: 11,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 2****Multifleet SHPD 15W-40***Check every 10 hours, change every 250 hours***DIFFERENTIAL**

Capacity: 9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 250 hours, change every 6 months/ 1000 hours***HUB REDUCTIONS FRONT****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90****HUB REDUCTIONS REAR**

Capacity: 1,3 liter (each hub)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 250 hours, change every 6 months/ 1000 hours***TRANSMISSION**

Capacity: 19 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032****PRODUCT RECOMMENDATION 2****ATF Almirol***Check every 250 hours, change every 6 months/ 1000 hours*

GRADALL MATERIAL HANDLERS 534B-8

**HYDRAULIC SYSTEM**

Capacity: 151 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

*Check every 10 hours, change every 2000 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

*Check every 50 hours***COOLING SYSTEM**

Capacity: 23 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

*Check every 10 hours, change every 2000 hours***BOOM BEARING PADS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2	Q5 MP Calcep Grease EP 2

Check every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.