

HAKO/MULTICAR CITYMASTER

CITYMASTER 1200 CITYCLEANER (1433.62)

YANMAR 4TNV88



ENGINE Yanmar 4TNV88
Capacity: 8,6 liter, Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Check every 8 hours, change every 12 months/ 250 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

PRODUCT RECOMMENDATION 2

Multifleet SCD 30*Check every 8 hours, change every 12 months/ 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40*Check every 8 hours, change every 12 months/ 250 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20

PRODUCT RECOMMENDATION 2

Multifleet SCD 10W*Check every 8 hours, change every 12 months/ 250 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Change every 50 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

PRODUCT RECOMMENDATION 2

Multifleet SCD 30*Change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40*Change every 50 hours*

HAKO/MULTICAR CITYMASTER

CITYMASTER 1200 CITYCLEANER (1433.62)

YANMAR 4TNV88



USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 20W-20	Multifleet SCD 10W	
<i>Change every 50 hours</i>		

HYDRAULIC SYSTEM		
Capacity: 45 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
<i>Check every 50 hours, change every 1000 hours/ 24 months</i>		

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		
<i>Check every 50 hours, change every 1000 hours/ 24 months</i>		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 22	Perlus AF 32	
<i>Check every 50 hours, change every 1000 hours/ 24 months</i>		

HYDRAULIC BRAKE SYSTEM		
Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-S DOT 4	Drauliquid DOT 3	
<i>Check every 8 hours, change every 24 months/ 1000 hours</i>		

GREASE POINTS/NIPPLES GENERAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

HAKO/MULTICAR CITYMASTER

CITYMASTER 1200 CITYCLEANER (1433.62)

YANMAR 4TNV88

**COOLING SYSTEM**

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15	Coolant SP 15+	Coolant SP 12

Check every 8 hours, change every 24 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.