

HAKO/MULTICAR CITYMASTER

CITYMASTER 2000 EURO 4 (1434.22) VW 2.0 TDI

**ENGINE CBKA**

Capacity: 4,3 liter, Filter capacity: 0,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30*Check every 8 hours, change every 12 months/ 300 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30*Change every 50 hours***DIFFERENTIAL REAR**

Capacity: 2,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 300 hours, change every 48 months/ 1200 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 50 hours***TRANSFER/REDUCTION GEARBOX**

Capacity: 1,15 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 300 hours, change every 48 months/ 1200 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 50 hours*

HAKO/MULTICAR CITYMASTER

CITYMASTER 2000 EURO 4 (1434.22) VW 2.0 TDI



HYDRAULIC SYSTEM

Capacity: 58 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---------------------------|--------------------------|
| Perlus Biosynth 46 | Perlus H 46 |

Check every 50 hours, change every 36 months/ 1200 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---------------------------|--------------------------|
| Perlus Biosynth 32 | Perlus H 32 |

Check every 50 hours, change every 36 months/ 1200 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| Perlus H 22 | |

Check every 50 hours, change every 36 months/ 1200 hours

| USE | CLIMATE |
|-------------------|----------|
| Biodegradable oil | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|---------------------------|--|
| Perlus Biosynth 46 | |

Check every 50 hours, change every 36 months/ 1200 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|---------------------------|--|
| Drauliquid DOT 5.1 | |

Check every 8 hours, change every 24 months

GREASE POINTS/NIPPLES CARDAN SHAFTS

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------------|------------------------------|
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

HAKO/MULTICAR CITYMASTER

CITYMASTER 2000 EURO 4 (1434.22) VW 2.0 TDI



GREASE POINTS/NIPPLES GENERAL

| USE | | CLIMATE |
|---------------------------------|------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |

COOLING SYSTEM

Capacity: 12 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 12 | | |

Check every 8 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.