

HAKO/MULTICAR CITYTRACK CITYTRACK

4200 DA (8010.01/02) YANMAR 4TNV88

**ENGINE** Yanmar 4TNV88

Capacity: 8,6 liter, Filter capacity: 0,4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Check every 8 hours, change every 12 months/ 250 hours*

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

PRODUCT RECOMMENDATION 2

Multifleet SCD 30*Check every 8 hours, change every 12 months/ 250 hours*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40*Check every 8 hours, change every 12 months/ 250 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20

PRODUCT RECOMMENDATION 2

Multifleet SCD 10W*Check every 8 hours, change every 12 months/ 250 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Change every 50 hours*

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

PRODUCT RECOMMENDATION 2

Multifleet SCD 30*Change every 50 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40*Change every 50 hours*

HAKO/MULTICAR CITYTRACK CITYTRACK 4200 DA (8010.01/02) YANMAR 4TNV88



| USE | | CLIMATE |
|------------------------------|---------------------------|---------|
| Initial service | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 20W-20 | Multifleet SCD 10W | |
| <i>Change every 50 hours</i> | | |

| HYDRAULIC SYSTEM | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |
| <i>Check every 8 hours, change every 24 months/ 1000 hours</i> | | |

| USE | | CLIMATE |
|--|--------------------------|---------|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 32 | Perlus H 32 | |
| <i>Check every 8 hours, change every 24 months/ 1000 hours</i> | | |

| USE | | CLIMATE |
|--|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 22 | | |
| <i>Check every 8 hours, change every 24 months/ 1000 hours</i> | | |

| USE | | CLIMATE |
|--|--|----------|
| Biodegradable oil | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |
| <i>Check every 8 hours, change every 24 months/ 1000 hours</i> | | |

| GREASE POINTS/NIPPLES GENERAL | | |
|-------------------------------|---------------------------------|------------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

HAKO/MULTICAR CITYTRACK CITYTRACK

4200 DA (8010.01/02) YANMAR 4TNV88

**COOLING SYSTEM**

Capacity: 7,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15****PRODUCT RECOMMENDATION 2****Coolant SP 15+****PRODUCT RECOMMENDATION 3****Coolant SP 12**

Check every 8 hours, change every 24 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.