PRODUCT RECOMMENDATION

HAKO/MULTICAR MULTICAR M27TL (4X2) VW 2.0 TDI (EURO 5) (WMU2M30E5BW270002 ->)

ENGINE CJDD
Capacity: 4,3 liter, Filter capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Helar SP LL-03 5W-30		

Check every 8 hours, change every 25000 km/ 12 months/ 500 hours

DIFFERENTIAL REAR
Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 25000 km/ 24 months/ 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 2500 km/ 50 hours

TRANSMISSION MANUAL W 32 S5-01/DK 5/1
Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	**SP Gear 5015**	**Gearlube GL-4 80W**

Check every 25000 km/ 500 hours, change every 75000 km/ 24 months/ 1500 hours

TRANSMISSION MANUAL W 32 S5/Nh7-01/DK 5/1
Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	**SP Gear 5015**	**Gearlube GL-4 80W**

Check every 25000 km/ 500 hours, change every 75000 km/ 24 months/ 1500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

HAKO/MULTICAR MULTICAR M27TL (4X2) VW 2.0 TDI (EURO 5) (WMU2M30E5BW270002 ->)

HYDRAULIC SYSTEM

Capacity: 70 liter (Hydraulic tank. Dual circuit hydraulics (Variant 03)), Capacity: 25 liter (Hydraulic tank. For electric tilt hydraulics EHK), Capacity: 70 liter (Hydraulic tank. Three circuit universal hydraulics (Variant 04))

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	**Perlus AF 46**	

Check every 50 hours, change every 25000 km/ 24 months/ 500 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Perlus H 32		

Check every 50 hours, change every 25000 km/ 24 months/ 500 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 22	**Perlus AF 32**	

Check every 50 hours, change every 25000 km/ 24 months/ 500 hours

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 50 hours, change every 25000 km/ 24 months/ 500 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		

Check every 50 hours, change every 75000 km/ 24 months/ 1500 hours

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		

Check every 50 hours, change every 75000 km/ 24 months/ 1500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

HAKO/MULTICAR MULTICAR M27TL (4X2) VW 2.0 TDI (EURO 5) (WMU2M30E5BW270002 ->)

GREASE POINTS/NIPPLES CARDAN SHAFTS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 50 hours

GREASE POINTS/NIPPLES GENERAL

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
HT Q9 High Grade Grease	**Labora Grease**	**Q5 MP Calcep Grease EP 2**

Change every 50 hours

COOLING SYSTEM
Capacity: 12 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 12		

Check every 50 hours, change every 75000 km/ 24 months/ 1500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367