

HAKO/MULTICAR MULTICAR M31BA (4X4)

IVECO F1CE3481R (EURO 5)

(WMU2M31E5DW000001 ->)



ENGINE Iveco F1CE3481R
Capacity: 5,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT

Capacity: 2,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 30000 km/ 24 months/ 600 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 2500 km/ 50 hours

DIFFERENTIAL REAR

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 30000 km/ 24 months/ 600 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 2500 km/ 50 hours

TRANSMISSION MANUAL WNV 32 S5 5/1

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 30000 km/ 600 hours, change every 60000 km/ 24 months/ 1200 hours

HAKO/MULTICAR MULTICAR M31BA (4X4)

IVECO F1CE3481R (EURO 5)

(WMU2M31E5DW000001 ->)

**TRANSMISSION MANUAL WV 32 S5/Nh7 5/1**

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 30000 km/ 600 hours, change every 60000 km/ 24 months/ 1200 hours

TRANSMISSION MANUAL WV32 S5 (4180) 5/1

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 30000 km/ 600 hours, change every 60000 km/ 24 months/ 1200 hours

HYDRAULIC SYSTEM

Capacity: 8 liter (Hydraulic tank. For electric tilt hydraulics EHK), Capacity: 70 liter (Hydraulic tank. Stationary hydraulics (Variant 02)), Capacity: 70 liter (Hydraulic tank. To operate all front-end and chassis attachments (Variant 07))

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Check every 50 hours, change every 24 months/ 30000 km

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 32	Perlus H 32	

Check every 50 hours, change every 24 months/ 30000 km

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		

Check every 50 hours, change every 24 months/ 30000 km

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 50 hours, change every 24 months/ 30000 km

HAKO/MULTICAR MULTICAR M31BA (4X4)

IVECO F1CE3481R (EURO 5)

(WMU2M31E5DW000001 ->)

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 5.1

Check every 50 hours, change every 60000 km/ 24 months/ 1200 hours

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 5.1

Check every 50 hours, change every 60000 km/ 24 months/ 1200 hours

GREASE POINTS/NIPPLES CARDAN SHAFTS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 2

MP Lithep Grease EP 2

Change every 50 hours

GREASE POINTS/NIPPLES GENERAL

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

PRODUCT RECOMMENDATION 2

Labora Grease

PRODUCT RECOMMENDATION 3

Q5 MP Calcep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

Check every 50 hours, change every 60000 km/ 24 months/ 1200 hours

PRODUCT RECOMMENDATION

HAKO/MULTICAR MULTICAR M31BA (4X4) IVECO F1CE3481R (EURO 5) (WMU2M31E5DW000001 ->)



HYDRAULIC SYSTEM STEERING

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

Check every 50 hours, change every 60000 km/ 24 months/ 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.