## HAKO/MULTICAR MULTICAR M31H (4X2) IVECO F1CE3481T (EURO 5) (WMU2M31E5DW000003 ->)



**ENGINE** Iveco F1CE3481T Capacity: 5,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR Capacity: 4,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
Change every 30000 km/ 24 months/ 600 hours			
USE		CLIMATE	

Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Initial service		Moderate
002		OLIMITA E

Change every 2500 km/50 hours

TRANSFERBOX Capacity: 2,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 30000 km/ 600 hours, change every 60000 km/ 24 months/ 1200 hours

## HAKO/MULTICAR MULTICAR M31H (4X2) IVECO F1CE3481T (EURO 5) (WMU2M31E5DW000003 ->)



USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Check every 50 hours, change every	24 months/ 30000 km	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 32	Perlus H 32	
Check every 50 hours, change every	24 months/ 30000 km	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		
Check every 50 hours, change every	24 months/ 30000 km	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 50 hours, change every	24 months/ 30000 km	

HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 5.1	
Charle avery 50 hours shangs avery 60000 km/24 months/15	200 hours

Check every 50 hours, change every 60000 km/24 months/ 1200 hours

GREASE POINTS/NIPPLES CARDAN SHAFTS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
Change every 50 hours			

## HAKO/MULTICAR MULTICAR M31H (4X2) IVECO F1CE3481T (EURO 5) (WMU2M31E5DW000003 ->)



GREASE POINTS/NIPPLES GENERAL			
USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2	
Change every 50 hours			

COOLING SYSTEM Capacity: 15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	

Check every 50 hours, change every 60000 km/24 months/1200 hours

HYDRAULIC SYSTEM STEERING Capacity: 3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	
Check every 50 hours, change every 60000 km/24 months/ 1200 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.