

HAMM DOUBLE DRUM COMPACTORS

DV/HD DV 70 VO DEUTZ TCD2012 L04 2V

TIER III (H1910115 ->)



ENGINE Deutz TCD 2012 L04 2V
Capacity: 11,5 liter (Service fill)

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Change every 500 hours

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40

Change every 500 hours

HYDRAULIC SYSTEM

Capacity: 45 liter (Hydraulic tank)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Perlus H 68

Change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

PRODUCT RECOMMENDATION 2

Perlus H 46

Change every 2000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Perlus Biosynth 32

PRODUCT RECOMMENDATION 2

Perlus H 32

Change every 2000 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Perlus H 22

Change every 2000 hours

HAMM DOUBLE DRUM COMPACTORS

DV/HD DV 70 VO DEUTZ TCD2012 L04 2V

TIER III (H1910115 ->)



USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Change every 2000 hours

USE		CLIMATE
Biodegradable oil		Cold
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 32		

Change every 2000 hours

COOLING SYSTEM

Capacity: 16 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.