## HAMM DOUBLE DRUM COMPACTORS DV/HD HD 13 DEUTZ F2L 2011 (H1393612 ->)



<b>ENGINE</b> Deutz F2L-2011 Capacity: 6 liter (Service fill)			
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1			
Multifleet SHPD 20W-50			
Change every 50 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	
Change every 50 hours			
USE		CLIMATE	
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Mediterranean	
PRODUCT RECOMMENDATION 1			
Multifleet SHPD 20W-50			
Change every 1000 hours			
USE		CLIMATE	
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	
Change every 1000 hours			

HYDRAULIC SYSTEM Capacity: 35 liter				
USE		CLIMATE		
Normal		Tropical		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Perlus H 68	Perlus AF 68	Perlus AF 100		
Change every 2000 hours				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Perlus H 46	Perlus AF 46			
Change every 2000 hours				

## HAMM DOUBLE DRUM COMPACTORS DV/HD HD 13 DEUTZ F2L 2011 (H1393612 ->)



USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 22	Perlus AF 32	
Change every 2000 hours		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 2000 hours		
USE		CLIMATE
Biodegradable oil		Cold
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 32		
Change every 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.