HAMM DOUBLE DRUM COMPACTORS DV/HD HD 130 DEUTZ BF4M1013E (H1630001 ->)



ENGINE Deutz BF4M-1013E Capacity: 12,5 liter (Service fill)		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 50 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Change every 50 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 500 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40
Change every 500 hours		

PRODUCT RECOMMENDATION

HAMM DOUBLE DRUM COMPACTORS DV/HD HD 130 DEUTZ BF4M1013E (H1630001 ->)



HYDRAULIC SYSTEM Capacity: 70 liter (Hydraulic tank)		
USE	CLIM	IATE
Normal	Мос	derate
PRODUCT RECOMMENDATION 1		
Perlus HCD 46		
Change every 2000 hours		
USE	CLIM	IATE
Biodegradable oil	Мос	derate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 2000 hours		
USE	CLIM	IATE
Biodegradable oil	Cole	ld
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 32		
Change every 2000 hours		

COOLING SYSTEM Capacity: 21,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

VIBRATOR Capacity: 1,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.