## HAMM DOUBLE DRUM COMPACTORS DV/HD HD 70 DEUTZ TD2011 L04W TIER 4I



(H1870614 ->) (2012 AND AFTER)

<b>ENGINE</b> Deutz TD 2011 L04W Capacity: 10 liter (Service fill)		
USE		CLIMATE
Alternative, fuel sulfur level < 0,0015 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40
Change every 500 hours		

**HYDRAULIC SYSTEM** Capacity: 45 liter (Hydraulic tank) CLIMATE Normal Tropical PRODUCT RECOMMENDATION 1 Perlus H 68 Change every 2000 hours USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 **Perlus Biosynth 46** Perlus H 46 Change every 2000 hours USE CLIMATE Normal Cold PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Perlus H 32 Perlus Biosynth 32 Change every 2000 hours USE CLIMATE Normal Arctic PRODUCT RECOMMENDATION 1 Perlus H 22 Change every 2000 hours USE CLIMATE Biodegradable oil Moderate PRODUCT RECOMMENDATION 1 Perlus Biosynth 46

Change every 2000 hours

PRODUCT RECOMMENDATION

## HAMM DOUBLE DRUM COMPACTORS DV/HD HD 70 DEUTZ TD2011 L04W TIER 4I



(H1870614 ->) (2012 AND AFTER)

USE		CLIMATE
Biodegradable oil		Cold
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 32		
Change every 2000 hours		

## **COOLING SYSTEM**

Capacity: 11 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## **VIBRATOR**

Capacity: 7 liter (each drum)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.