HAMM DOUBLE DRUM COMPACTORS DV/HD HD 90K DEUTZ BF4M1013E (H1530044 ->)



ENGINE Deutz BF4M-1013E Capacity: 12,5 liter (Service fill)			
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1			
Multifleet SHPD 20W-50			
Change every 50 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	
Change every 50 hours			
USE		CLIMATE	
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Mediterranean	
PRODUCT RECOMMENDATION 1			
Multifleet SHPD 20W-50			
Change every 500 hours			
USE		CLIMATE	
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	
Change every 500 hours			

PRODUCT RECOMMENDATION

HAMM DOUBLE DRUM COMPACTORS DV/HD HD 90K DEUTZ BF4M1013E (H1530044 ->)



HYDRAULIC SYSTEM Capacity: 70 liter (Hydraulic tank)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus HCD 46	
Change every 2000 hours	
USE	CLIMATE
Biodegradable oil	Moderate
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 46	
Change every 2000 hours	
USE	CLIMATE
Biodegradable oil	Cold
PRODUCT RECOMMENDATION 1	
Perlus Biosynth 32	
Change every 2000 hours	

COOLING SYSTEM Capacity: 21,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

VIBRATOR Capacity: 11 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.