# HAMM SINGLE DRUM COMPACTORS 3414 HT P DEUTZ BF4M2012C (H1600458 ->)



<b>ENGINE</b> Deutz BF4M-2012C Capacity: 9,5 liter (Service fill)		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 50 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Change every 50 hours	'	
USE		CLIMATE
Normal, fuel sulfur level <0,5 %,	ambient temperature > -10°C	Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 500 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %,	ambient temperature > -10°C	Moderate
	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Kroontrak CVT 10W-40		
Kroontrak CVT 10W-40  Change every 500 hours  DIFFERENTIAL		
Change every 500 hours  DIFFERENTIAL Capacity: 14 liter		Agridiesel MSP 15W-40
Kroontrak CVT 10W-40  Change every 500 hours  DIFFERENTIAL Capacity: 14 liter  USE		Agridiesel MSP 15W-40  CLIMATE
Change every 500 hours  DIFFERENTIAL Capacity: 14 liter USE Normal		Agridiesel MSP 15W-40
Kroontrak CVT 10W-40  Change every 500 hours  DIFFERENTIAL Capacity: 14 liter  USE		Agridiesel MSP 15W-40  CLIMATE
Change every 500 hours  DIFFERENTIAL Capacity: 14 liter  USE Normal  PRODUCT RECOMMENDATION 1  Gearlube LS 80W-90	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40  CLIMATE
Change every 500 hours  DIFFERENTIAL Capacity: 14 liter USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90  Check every 250 hours, change every	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40  CLIMATE  Moderate
Change every 500 hours  DIFFERENTIAL Capacity: 14 liter  USE Normal  PRODUCT RECOMMENDATION 1  Gearlube LS 80W-90	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40  CLIMATE
Change every 500 hours  DIFFERENTIAL Capacity: 14 liter  USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90  Check every 250 hours, change every USE	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40  CLIMATE  Moderate  CLIMATE

### **HYDRAULIC SYSTEM**

Change every 500 hours

Capacity: 50 liter (Hydraulic tank)

## HAMM SINGLE DRUM COMPACTORS 3414 HT P DEUTZ BF4M2012C (H1600458 ->)



USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 68	Perlus AF 68	Perlus AF 100
Change every 2000 hours		
USE		CLIMATE
Normal	_	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
Change every 2000 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 22	Perlus AF 32	
Change every 2000 hours		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 2000 hours		
USE		CLIMATE
Biodegradable oil		Cold
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 32		
Change every 2000 hours		

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		

PRODUCT RECOMMENDATION

## HAMM SINGLE DRUM COMPACTORS 3414 HT P DEUTZ BF4M2012C (H1600458 ->)



**COOLING SYSTEM** 

Capacity: 16 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

#### **DRUM GEARBOX**

Capacity: 2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

#### **VIBRATOR**

Capacity: 1,6 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.