## HAMM SINGLE DRUM COMPACTORS 3516 DEUTZ BF6M2012C TIER II (H2150001 ->)



Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Normal, fuel sulfur level <0,5 %, am	bient temperature > -10°C	Moderate	
USE		CLIMATE	
Change every 500 hours			
PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50			
use Normal, fuel sulfur level <0,5 %, am	bient temperature > -10°C	CLIMATE Mediterranean	
ENGINE Deutz BF6M-2012C Capacity: 15,5 liter (Service fill)			

Change every 500 hours

DIFFERENTIAL Capacity: 14 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 250 hours, change every 1000 hours

USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
0h	·

Change every 500 hours

HYDRAULIC SYSTEM Capacity: 50 liter (Hydraulic tank)	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Perlus H 68	

Change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Change every 2000 hours		

Change every 2000 hours

## HAMM SINGLE DRUM COMPACTORS 3516 DEUTZ BF6M2012C TIER II (H2150001 ->)



USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 32	Perlus H 32	
Change every 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		
Change every 2000 hours		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 2000 hours		
USE		CLIMATE
Biodegradable oil		Cold
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 32		
Change every 2000 hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

### COOLING SYSTEM

Capacity: 22 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### DRUM GEARBOX

#### Capacity: 3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

#### VIBRATOR

#### Capacity: 1,6 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

# HAMM SINGLE DRUM COMPACTORS 3516 DEUTZ BF6M2012C TIER II (H2150001 ->)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.