

HANGCHA FORKLIFT TRUCKS N-SERIES

CPCD30N ISUZU 4JG2



ENGINE Isuzu 4JG2
Capacity: 6,5-7,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|-------------------------------|
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 |

Check every 8 hours, change every 100 hours

DIFFERENTIAL FRONT
Capacity: 8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1200 hours

TRANSMISSION
Capacity: 7 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| SP Matic 2032 | ATF Almirol | |

Change every 1200 hours

HYDRAULIC SYSTEM
Capacity: 45-50 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 32 | | |

Change every 1200 hours

HYDRAULIC BRAKE SYSTEM
Capacity: 1,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Drauliquid DOT 3 | | |

Change every 1200 hours

HANGCHA FORKLIFT TRUCKS N-SERIES

CPCD30N ISUZU 4JG2



GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 8 hours, change every 100 hours

COOLING SYSTEM

Capacity: 10-11 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.