## **HANIX TRACKED EXCAVATORS H15B**



| ENGINE                   |                          |               |
|--------------------------|--------------------------|---------------|
| USE                      |                          | CLIMATE       |
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |               |
| Change every 250 hours   |                          |               |
| USE                      |                          | CLIMATE       |
| Initial service          |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |               |
| Change every 50 hours    |                          |               |

| HYDRAULIC SYSTEM         |               |
|--------------------------|---------------|
| USE                      | CLIMATE       |
| Normal                   | Mediterranean |
| PRODUCT RECOMMENDATION 1 |               |
| Perlus H 46              |               |
| Change every 1000 hours  |               |
| USE                      | CLIMATE       |
| Normal                   | Moderate      |
| PRODUCT RECOMMENDATION 1 |               |
| Perlus H 32              |               |

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| FRONT IDLERS             |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Multifleet SCD 30        |          |
|                          |          |

Change every 1000 hours

## HANIX TRACKED EXCAVATORS H15B



| SLEW REDUCTION GEARBOX         |          |  |
|--------------------------------|----------|--|
| USE                            | CLIMATE  |  |
| Normal                         | Moderate |  |
| PRODUCT RECOMMENDATION 1       |          |  |
| Multifleet SCD 30              |          |  |
| Change every 1000 hours        |          |  |
| USE                            | CLIMATE  |  |
| Initial service                | Moderate |  |
| PRODUCT RECOMMENDATION 1       |          |  |
| Multifleet SCD 30              |          |  |
| Change every 200 hours         |          |  |
|                                |          |  |
| TRACK DRIVE GEARBOXES          |          |  |
| USE                            | CLIMATE  |  |
| Normal                         | Moderate |  |
| PRODUCT RECOMMENDATION 1       |          |  |
| Multifleet SCD 30              |          |  |
| Change every 1000 hours        |          |  |
| USE                            | CLIMATE  |  |
| Initial service                | Moderate |  |
| PRODUCT RECOMMENDATION 1       |          |  |
| Multifleet SCD 30              |          |  |
| Change every 200 hours         |          |  |
|                                |          |  |
| TRACK ROLLERS                  |          |  |
| USE                            | CLIMATE  |  |
| Normal                         | Moderate |  |
| PRODUCT RECOMMENDATION 1       |          |  |
| Multifleet SCD 30              |          |  |
|                                |          |  |
| TRAVEL MOTOR REDUCTION GEARBOX |          |  |
| USE                            | CLIMATE  |  |
| Normal                         | Moderate |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90