

HANIX TRACKED EXCAVATORS H30C (2011 AND AFTER)



ENGINE Mitsubishi S3L2
Capacity: 4,5 liter

USE Normal		CLIMATE Moderate
---------------	--	---------------------

PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Dieselfleet LSP Ultra 10W-30
---	---	---

Change every 250 hours

USE Initial service		CLIMATE Moderate
------------------------	--	---------------------

PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Dieselfleet LSP Ultra 10W-30
---	---	---

Change every 50 hours

TRANSMISSION/HYDRAULIC SYSTEM
Capacity: 50,5 liter

USE Normal		CLIMATE Moderate
---------------	--	---------------------

PRODUCT RECOMMENDATION 1 Perlus H 32		
--	--	--

Change every 1000 hours

GREASE POINTS/NIPPLES

USE Normal		CLIMATE Moderate
---------------	--	---------------------

PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2
--	---	--

COOLING SYSTEM

USE Normal		CLIMATE Moderate
---------------	--	---------------------

PRODUCT RECOMMENDATION 1 Coolant -38 Organic NF	PRODUCT RECOMMENDATION 2 Coolant -26	
---	--	--

Change every 500 hours

HANIX TRACKED EXCAVATORS H30C (2011 AND AFTER)



CARRIER ROLLERS

Capacity: 0,07 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 1000 hours

TRACK IDLERS

Capacity: 0,08 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 2000 hours

TRACK ROLLERS

Capacity: 0,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 1000 hours

TRAVEL REDUCTION GEARBOX

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.