## HITACHI WHEELED EXCAVATORS EX 135W



(1999-2002)

<b>ENGINE</b> Cummins 4BT3.9C Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change eveny 250 hours/ 6 months	·	·

Change every 250 hours/ 6 months

DIFFERENTIAL FRONT	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

DIFFERENTIAL REAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

GEARBOX	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 2000 hours	'

Gearlube LS 80W-90	
PRODUCT RECOMMENDATION 1	
Normal	Moderate
USE	CLIMATE
HUB REDUCTIONS	

## **HITACHI WHEELED EXCAVATORS EX 135W**



(1999-2002)

HYDRAULIC SYSTEM Capacity: 110 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 2500 hours	·

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

GREASE POINTS/NIPPLES SWING INTERNAL GEAR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			

COOLING SYSTEM Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

SWING REDUCTION UNIT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 2000 hours	1	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.