

# HITACHI WHEELED LOADERS LX/ZW ZW220-5B CUMMINS QSB6.7 (2013 AND AFTER)



**ENGINE** Cummins QSB6.7  
Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP Ultra FE 5W-30**

PRODUCT RECOMMENDATION 2

**Agridiesel MSP 15W-40**

PRODUCT RECOMMENDATION 3

**Dieselfleet LSP Ultra 10W-30**

*Check every 8 hours, change every 500 hours*

**DIFFERENTIAL FRONT**

Capacity: 32 liter (+ hub reductions)

We are unable to give a standard recommendation for this component. Please contact our service department.

**DIFFERENTIAL REAR**

Capacity: 32 liter (+ hub reductions)

We are unable to give a standard recommendation for this component. Please contact our service department.

**HUB REDUCTIONS FRONT**

We are unable to give a standard recommendation for this component. Please contact our service department.

**HUB REDUCTIONS REAR**

We are unable to give a standard recommendation for this component. Please contact our service department.

**TRANSMISSION + TORQUE CONVERTER**

Capacity: 40 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

*Check every 8 hours, change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

*Check every 8 hours, change every 100 hours*

# HITACHI WHEELED LOADERS LX/ZW

## ZW220-5B CUMMINS QSB6.7 (2013 AND AFTER)



### HYDRAULIC SYSTEM

Capacity: 190 liter (Change capacity)

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 8 hours, change every 4000 hours*

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

### COOLING SYSTEM

Capacity: 28 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*