

# HITACHI TRACKED EXCAVATORS EX EX 135 (1998-2002)



**ENGINE** Iveco 8045.25T  
Capacity: 9,5 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40**

*Check every 8 hours, change every 500 hours*

**HYDRAULIC SYSTEM**  
Capacity: 120 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 46**

*Change every 2500 hours*

## GREASE POINTS/NIPPLES SWING INTERNAL GEAR

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

## PRESSURE GREASE FITTING

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

**COOLING SYSTEM**  
Capacity: 16 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF**

# HITACHI TRACKED EXCAVATORS EX EX 135 (1998-2002)



## PUMP DRIVE UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

## SWING REDUCTION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 hours*

## TRAVEL REDUCTION UNIT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*