

HITACHI TRACKED EXCAVATORS EX EX 8

(1994-1994)



ENGINE Isuzu
Capacity: 1,9 liter

USE
Normal

CLIMATE
Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Check every 8 hours, change every 100 hours

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 8 hours, change every 100 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Check every 8 hours, change every 100 hours

USE
Normal

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Check every 8 hours, change every 100 hours

USE
Initial service

CLIMATE
Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Check every 8 hours, change every 50 hours

USE
Initial service

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 8 hours, change every 50 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Check every 8 hours, change every 50 hours

HITACHI TRACKED EXCAVATORS EX EX 8

(1994-1994)



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 8 hours, change every 50 hours

HYDRAULIC SYSTEM		
Capacity: 13 liter (Change capacity)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 1000 hours

COOLING SYSTEM		
Capacity: 2,3 liter		
USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 8 hours, change every 24 months/ 4000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 8 hours, change every 6 months

FRONT JOINT PINS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SWING BEARING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

HITACHI TRACKED EXCAVATORS EX EX 8

(1994-1994)



SWING GEAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

TRAVEL REDUCTION UNIT

Capacity: 0,33 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.