

# HITACHI TRACKED EXCAVATORS ZX / ZAXIS ZAXIS / ZX 55U-5 (2013 AND AFTER)



**ENGINE** Yanmar 4TNV88  
Capacity: 7,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP Ultra FE 5W-30**

PRODUCT RECOMMENDATION 2

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Kroontrak MTH 10W-30**

*Check every 8 hours, change every 500 hours*

## HYDRAULIC SYSTEM

Capacity: 66 liter (Change capacity)

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 46**

*Check every 8 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

*Change every 8 hours*

## COOLING SYSTEM

Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

## TRAVEL REDUCTION UNIT

Capacity: 0,9 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 500 hours, change every 1000 hours*

# HITACHI TRACKED EXCAVATORS ZX / ZAXIS ZAXIS / ZX 55U-5 (2013 AND AFTER)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*