Check every 8 hours, change every 500 hours

HITACHI TRACKED EXCAVATORS ZX / ZAXIS ZAXIS / ZX 80SBLC (2004-2007)



ENGINE Isuzu 4BG1 XABF Capacity: 12 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30		
Check every 8 hours, change every 500 hours				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40		
Check every 8 hours, change every 500 hours				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1				
Multifleet SCD 10W				

HYDRAULIC SYSTEM Capacity: 100 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 1500 hours/ 12 months	

PRODUCT RECOMMENDATION 2	T RODGET RECOMMENDATION 3
DD OD HOT DECOMMEND A TION O	PRODUCT RECOMMENDATION 3
	Moderate
	CLIMATE

HITACHI TRACKED EXCAVATORS ZX / ZAXIS ZAXIS / ZX 80SBLC (2004-2007)



TRAVEL REDUCTION UNIT Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.