HYDREMA BACKHOE LOADERS 614 PERKINS 1004-40HR (1994-1998)



ENGINE Capacity: 5,5 liter	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Multifleet SCD 40	

Check every 10 hours, change every 400 hours

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30

Check every 10 hours, change every 400 hours

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SHPD 10W-40	

Check every 10 hours, change every 400 hours

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Agrifluid HT

Check every 200 hours, change every 1000 hours/ 12 months

DIFFERENTIAL REAR Capacity: 8,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT
Check every 200 hours, change ever	v 1000 hours/ 12 months	'

HYDREMA BACKHOE LOADERS 614 PERKINS 1004-40HR (1994-1998)



HUB REDUCTIONS FRONT Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Check every 200 hours, change every 1000 hours/12 months

HUB REDUCTIONS REAR Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT

Check every 200 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Check every 10 hours, change every	1000 hours/ 12 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Check every 10 hours, change every	1000 hours/ 12 months	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

HYDREMA BACKHOE LOADERS 614 PERKINS 1004-40HR (1994-1998)



BACKHOE ROTATING SYSTEM Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP 150		
Check every 400 hours, change every 120	0 hours	
HYDRAULIC SYSTEM Capacity: 80 liter		

Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check every 40 hours, change every 24 m	onths/ 2000 hours	
USE		CLIMATE
use Normal		CLIMATE Moderate

CLIMATE

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours change ever	v 2000 hours/24 months	·

Check every 10 hours, change every 2000 hours/24 months

Check every 40 hours, change every 24 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.