HYUNDAI FORKLIFT TRUCKS, ELECTRIC B/BC/BCS/BH/BHA/BR/BRJ/BT/BTR/HBF/HBR 14BRJ-7



HYDRAULIC SYSTEM Capacity: 28 liter (Hydraulic tank (TF 700~TF 800)), Capacity: 32 liter (Hydraulic tank (TF 850)), Capacity: 25 liter (Hydraulic tank (~TF 670))			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Perlus H 68			
Check every 10 hours, change every 2000	hours		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 46	Perlus H 32		
Check every 10 hours, change every 2000	hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

DRIVE UNIT Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.