

HYUNDAI FORKLIFT TRUCKS, ELECTRIC B/BC/BCS/BH/BHA/BR/BRJ/BT/BTR/HBF/HBR 30BH-7



DIFFERENTIAL FRONT

Capacity: 5,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HYDRAULIC SYSTEM

Capacity: 25,5 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	

Check every 10 hours, change every 2000 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 10 hours, change every 6 months/ 1000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

HYUNDAI FORKLIFT TRUCKS, ELECTRIC B/BC/BCS/BH/BHA/BR/BRJ/BT/BTR/HBF/HBR 30BH-7



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.