HYUNDAI MINI EXCAVATORS, TRACKED R15 -> R80 R17Z-9A KUBOTA D902



ENGINE Kubota D902 Capacity: 3,7 liter		
USE		CLIMATE
Alternative, fuel sulfur level < 0,0015	%	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

HYDRAULIC SYSTEM Capacity: 23 liter (Hydraulic system including tank), Capacity: 13 liter (Hydraulic tank)				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Perlus H 68				
	- 			
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Perlus H 46				
USE		CLIMATE		
Normal		Cold		
PRODUCT RECOMMENDATION 1				
Perlus H 15				

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Grease EP 1			

HYUNDAI MINI EXCAVATORS, TRACKED R15 -> R80 R17Z-9A KUBOTA D902



COOLING SYSTEM Capacity: 3,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

TRACK DRIVE GEARBOXES Capacity: 0,33 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.