

# HYUNDAI WHEELED LOADERS HL

## HL730TM-7 (2004-2007)



**ENGINE** Cummins B3.9C  
Capacity: 11 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40**

*Check every 10 hours, change every 250 hours*

**DIFFERENTIAL FRONT LIMITED SLIP**  
Capacity: 18,4 liter (+ hub reductions)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 250 hours, change every 1000 hours*

**DIFFERENTIAL REAR**  
Capacity: 18,4 liter (+ hub reductions)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 250 hours, change every 1000 hours*

### HUB REDUCTIONS FRONT

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 250 hours, change every 1000 hours*

### HUB REDUCTIONS REAR

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 250 hours, change every 1000 hours*

# HYUNDAI WHEELED LOADERS HL

## HL730TM-7 (2004-2007)



**TRANSMISSION** Powershift  
Capacity: 20 liter

| USE                         |                             | CLIMATE                       |
|-----------------------------|-----------------------------|-------------------------------|
| Normal                      |                             | Moderate                      |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Check every 10 hours, change every 1000 hours*

### HYDRAULIC SYSTEM

Capacity: 90 liter (Hydraulic tank), Capacity: 125 liter (System)

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Perlus H 68</b>       |  |               |

*Check every 10 hours, change every 2000 hours*

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus H 32</b>       |          |

*Check every 10 hours, change every 2000 hours*

### GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Mediterranean                |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Change every 50 hours*

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Gear Grease EP 1</b>  |  |          |

*Change every 50 hours*

# HYUNDAI WHEELED LOADERS HL HL730TM-7 (2004-2007)

**COOLING SYSTEM**

Capacity: 30 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 10 hours, change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*