

HYUNDAI WHEELED LOADERS HL HL740TM-9 CUMMINS QSB6.7 (2010 AND AFTER)



ENGINE Cummins QSB6.7
Capacity: 18 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|------------------------------|-------------------------------------|
| Agrisynth MSP 10W-40 | Agridiesel MSP 15W-40 | Dieselfleet LSP Ultra 10W-30 |

Check every 10 hours, change every 500 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------------|--------------------------------------|-------------------------------|
| Agrisynth LSP Ultra 10W-40 | Armado Synth LSP Ultra 10W-40 | Armado Synth MSP 5W-40 |

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT LIMITED SLIP
Capacity: 21,8 liter (+ hub reductions)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Change every 1000 hours

DIFFERENTIAL REAR
Capacity: 21,8 liter (+ hub reductions)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Change every 1000 hours

HUB REDUCTIONS FRONT

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Change every 1000 hours

HYUNDAI WHEELED LOADERS HL HL740TM-9 CUMMINS QSB6.7 (2010 AND AFTER)



HUB REDUCTIONS REAR

| USE | | CLIMATE |
|--------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |
| <i>Change every 1000 hours</i> | | |

TRANSMISSION Powershift Capacity: 25 liter

| USE | | CLIMATE |
|--------------------------------|-----------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |
| <i>Change every 1000 hours</i> | | |

HYDRAULIC SYSTEM

Capacity: 151 liter (Hydraulic tank), Capacity: 184 liter (System)

| USE | | CLIMATE |
|--|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 68 | | |
| <i>Check every 10 hours, change every 2000 hours</i> | | |

| USE | | CLIMATE |
|--|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus H 46 | Perlus H 32 | |
| <i>Check every 10 hours, change every 2000 hours</i> | | |

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|------------------------------|---------------------------------|------------------------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| <i>Change every 50 hours</i> | | |

| USE | | CLIMATE |
|------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Grease EP 1 | | |
| <i>Change every 50 hours</i> | | |

HYUNDAI WHEELED LOADERS HL HL740TM-9 CUMMINS QSB6.7 (2010 AND AFTER)

**COOLING SYSTEM**

Capacity: 34 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Check every 10 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.