HYUNDAI WHEELED LOADERS HL HL757TM-7 -> 0114 (2004-2008)



ENGINE Cummins QSB5.9C Capacity: 16 liter		O. MATE
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT Volvo Capacity: 29 liter (+ hub reductions)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 250 hours, change every 1500 hours		

Normal Mo	LIMATE
	1oderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 250 hours, change every 1500 hours

HUB REDUCTIONS FRONT		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
01 1 0501		

Check every 250 hours, change every 1500 hours

HUB REDUCTIONS REAR		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 250 hours, change every 1500 hours	1	

HYUNDAI WHEELED LOADERS HL HL757TM-7 -> 0114 (2004-2008)



TRANSMISSION Powershift Capacity: 43 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 1000 hours

HYDRAULIC SYSTEM Capacity: 130 liter (Hydraulic tank), Capacity: 175 liter (System)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Check every 10 hours, change every 2000 hours		
USE		CLIMATE
Manus al		Madausta

Normal Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2
Perlus H 46 Perlus H 32

Check every 10 hours, change every 2000 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		
Change every 50 hours		

HYUNDAI WHEELED LOADERS HL HL757TM-7 -> 0114 (2004-2008)



COOLING SYSTEM Capacity: 35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every	/ 2000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.