

HYUNDAI TRACKED EXCAVATORS HX HX220L CUMMINS QSB6.7 (EU STAGE IV/TIER 4F) (2015 AND AFTER)



ENGINE Cummins QSB6.7
Capacity: 23,1 liter

USE

Alternative, fuel sulfur level < 0,0015 %

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40**FINAL DRIVE TRANSMISSIONS**

Capacity: 6 liter (each)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140**USE**

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90**HYDRAULIC SYSTEM**

Capacity: 275 liter (Hydraulic system including tank), Capacity: 160 liter (Hydraulic tank)

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 68**USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46**USE**

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1

Perlus H 15

HYUNDAI TRACKED EXCAVATORS HX HX220L CUMMINS QSB6.7 (EU STAGE IV/TIER 4F) (2015 AND AFTER)



GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

COOLING SYSTEM

Capacity: 40 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

Capacity: 27 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

SWING REDUCTION GEARBOX

Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.