HYUNDAI TRACKED EXCAVATORS R110 -> R140LCM-9S CUMMINS B3.9-C (2012 AND AFTER)



ENGINE Cummins B3.9C Capacity: 15,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30
Check every 10 hours, change every 500 h	nours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Check every 10 hours, change every 500 hours

HYDRAULIC SYSTEM Capacity: 124 liter (Hydraulic tank), Capacity: 210 liter (System)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Check every 10 hours, change every 2000 hours		
USE		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	
Check every 10 hours, change every 2000 hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours		·
105		

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Grease EP 1	
Change every 50 hours	·

HYUNDAI TRACKED EXCAVATORS R110 -> R140LCM-9S CUMMINS B3.9-C (2012 AND AFTER)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Coolant -26	

Check every 10 hours, change every 2000 hours

SWING GEAR		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
		•
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

SWING REDUCTION GEARBOX Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 50 hours, change every 1000 hours

TRACK DRIVE GEARBOXES Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	
01 10001	1	

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.