

HYUNDAI TRACKED EXCAVATORS R110 -> R260LC-9S CUMMINS B5.9 (2010 AND AFTER)



ENGINE Cummins B5.9
Capacity: 24 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 500 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Armado Synth LSP Ultra 10W-40	Armado Synth MSP 5W-40

Check every 10 hours, change every 500 hours

HYDRAULIC SYSTEM

Capacity: 165 liter (Hydraulic tank), Capacity: 285 liter (System)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	

Check every 10 hours, change every 2000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

Change every 50 hours

HYUNDAI TRACKED EXCAVATORS R110 -> R260LC-9S CUMMINS B5.9 (2010 AND AFTER)

**COOLING SYSTEM**

Capacity: 35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

*Check every 10 hours, change every 2000 hours***SWING REDUCTION GEARBOX**

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

*Check every 50 hours, change every 1000 hours***TRACK DRIVE GEARBOXES**

Capacity: 3,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.