

# IHI TRACKED EXCAVATORS 15VX

## WR003011 -> (2007 AND AFTER)



**ENGINE** Yanmar 3TNV70  
Capacity: 3,8 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20**

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40**

*Check every 10 hours, change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

*Check every 10 hours, change every 50 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20**

*Check every 10 hours, change every 50 hours*

# IHI TRACKED EXCAVATORS 15VX

## WR003011 -> (2007 AND AFTER)



### HYDRAULIC SYSTEM

Capacity: 23 liter, Capacity: 19 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 10 hours, change every 1000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Check every 10 hours, change every 1000 hours*

USE	CLIMATE
Breaker use	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Breaker use	Arctic

PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Check every 10 hours, change every 500 hours*

### GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

# IHI TRACKED EXCAVATORS 15VX

## WR003011 -> (2007 AND AFTER)

**COOLING SYSTEM**

Capacity: 3,6 liter

USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Check every 10 hours, change every 24 months*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 6 months/ 250 hours***IDLERS FRONT**

Capacity: 0,07 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

**TRACK ROLLERS**

Capacity: 0,03 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

**TRAVEL REDUCTION UNIT**

Capacity: 0,33 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Check every 500 hours, change every 1000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.