

# JCB WHEELED LOADERS (USA) 411 HT

## USA JCB ECOMAX STAGE IIIB/T4I (2014 AND AFTER)



**ENGINE** JCB Ecomax T4i  
Capacity: 14 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Armado Synth MSP 5W-40**

*Check every 10 hours, change every 500 hours/ 6 months*

**DIFFERENTIAL FRONT** JCB PD70  
Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Change every 500 hours*

**DIFFERENTIAL REAR** JCB PD70  
Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT**

*Change every 500 hours*

# JCB WHEELED LOADERS (USA) 411 HT

## USA JCB ECOMAX STAGE IIIB/T4I (2014 AND AFTER)

**TRANSMISSION** ZF 4WG115 4/3

Capacity: 27 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 2032</b>		

Check every 10 hours, change every 1000 hours/ 12 months

**HYDRAULIC SYSTEM**

Capacity: 155 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	

Check every 10 hours, change every 2000 hours/ 24 months

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		

Check every 10 hours, change every 2000 hours/ 24 months

**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	

**COOLING SYSTEM**

Capacity: 26 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.