JCB WHEELED LOADERS 418S CUMMINS QSB 6.7 TIER 4 (2012 AND AFTER)



| ENGINE Cummins QSB6.7 Capacity: 14 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Preferred | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agridiesel MSP 15W-40 | | |
| Check every 10 hours, change every 500 | hours/ 6 months | |
| USE | | CLIMATE |
| Alternative (acceptable) | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP 10W-40 | Agrisynth MSP 10W-40 | Agridiesel MSP 15W-40 |
| Check every 10 hours, change every 500 | hours/ 6 months | |

| DIFFERENTIAL FRONT JCB PD87 Capacity: 23 liter | | |
|--|-------------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 6 months/ 500 hours, change | e every 12 months/ 1000 hours | |

| DIFFERENTIAL REAR JCB PD87 Capacity: 23 liter | | |
|---|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

JCB WHEELED LOADERS 418S CUMMINS QSB 6.7 TIER 4 (2012 AND AFTER)



| TRANSMISSION ZF 6WG160 6/3 Capacity: 27 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Agrifluid HT |
| Check every 10 hours, change every | 1000 hours/ 12 months | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Agrifluid HT |
| Change every 100 hours | | , |

| HYDRAULIC SYSTEM | | |
|--|--------------------------|----------|
| Capacity: 155 liter | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |
| Change every 100 hours | | |
| USE | | CLIMATE |
| Flexible (max) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |
| Check every 10 hours, change every 200 | 00 hours/ 24 months | |
| USE | | CLIMATE |
| Flexible, fluid analysis | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus Biosynth 46 | Perlus H 46 | |
| Check every 6 months/ 500 hours | | |

| GREASE POINTS/NIPPLES | | | |
|--------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| HT Q9 High Grade Grease | Labora Grease | | |

JCB WHEELED LOADERS 418S CUMMINS QSB 6.7 TIER 4 (2012 AND AFTER)



| COOLING SYSTEM Capacity: 26 liter | | |
|--------------------------------------|------------------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |
| Check every 6 months/ 500 hours, | change every 24 months/ 2000 hours | ' |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.